PRESIDENT'S COMMISSION
ON THE
ASSASSINATION OF PRESIDENT KENNEDY ASSASSINATION OF PRESIDENT KENNEDY

200 Maryland Ave. N.E.

RICHARD B. RUSSELL
JOHN SHERMAN COOPER
HALE BOGGS
GERALD R. FORD
JOHN J. MCLOY
ALLEN W. DULLES

MAY 7 1964

Kr. J. Elgar Boover
Director, Federal Bureau of Investigation The transfer of the second of Washington, D. C.

Dear Mr. Hoover:

This Cormission has been making a careful study of the various motion picture films taken at the scene of the assassination. In this project we have had the valuable assistance of members of your Dureau, perticularly Inspector James R. Falley, Inspector Ico Consider and Special Agent Lyndal A. Shaneyfelt. As a result of the cooleration of your Bureau in the performance of certain additional investigation at the scene of the assassination. invectigation at the scene of the assassination.

I will personally be available to supervise this work and Will have such other staff members present as may be deemed necessary. Will neve such owner sums annuers process as we would hope to be able to perform this work in Dallas on May 18 and Lay 19. The purpose of this letter is to set forth the steps which we flet sie necessary to properly complete this project.

I. PRODUCE RANGE WITHIN WHICH THE FIRST TWO SHOTS OCCURRED

Cur exemination of the Zapruder films indicates that Governor Connally was hit at some point prior to frame 240. (All references to frames in the Zapruder films are on the basis of a numbering system worked out with FBI personnel who have been working on this project.) Doctors familiar with the Governor's wounds baye received the wound from a projectile fired from the sixth floor southeast corner window of the Texas School Book Depository Building. The Covernor feels he was hit at emproximately frame 230; some members of our staff feel that it could have been as late as 240. There is general consensus, however, that it could not have been later than 240. Governor and Mrs. Connally also testified that the Governor Was hit by the second shot.

South Transport in the second

The FBI laboratory examination of the Zapruder camera establishes that it operates at a speed of 18-1/3 frames' per second.

Weapons experts have testified that the minimum time required to operate the assassination weapon is 2-1/4 seconds. It would appear, therefore, that a minimum of 41 frames would have to elapse between the first and second shots (18-1/3 x 2-1/4).

The Commission is ewere that it is impossible to determine the exact point at which the first two shots were fired. We request the following on-site investigatory steps, however, in order to determine whether it was possible for a person located in the sixth floor southeast corner window of the TSED building to fire two shots at the Presidential car, the second of which occurred no later than frame 240:

(1) A point should be marked on the road corresponding

- (1) A point should be marked on the road corresponding to frame 109 on the Zamuder film, which is the last point at which the assessin could have fired from the window and still have been able to fire spain by frame 240. A car should be photographed on this spot from the sout where Zapruder was standing so that this photograph can. be compared with frame 199 to make certain that the location is accurate. This should be done with the Zapruder camera, which has been retained for this purpose. A Polaroid should also be used for immediate comparison.
- (2) After a car has been placed at this point on the road it should be photographed from the assassination window to determine whether the assassin had a clear shot at the occupants of the rear seat, with particular reference to the tree which at mint blocks the view from this window.
- when viewed from the vindow, the car should be moved forward to
 the point at which there is a first clear view from the window and when viewed from the vindow, who can be seen the point at which there is a first clear view from the window and photographed at this point from both the window and from the place where Zemmier was standing so that we may determine what from in the Eagruler film corresponds with this location.
- (b) If the car has in fact passed beyond the tree at freme 199, it should be moved back to the point where it first cleared the tree and photographed from the window and the Zepruder location to establish the corresponding frame reference.
 - (5) The car should also be placed at the point where And the state of t there is the lest clear shot before it goes behind the tree and photographed from the window and the Zapruder location to determine the freme reference at this point. Commence of the second

and the state of the second second

(6) All the above points should be mapped on a survey.

Lineal distances should be measured on the ground between these various points. Trigonometric readings should be taken to determine the distances from these various points to the assessination window and the surveyor should also determine the angle with the horizonal which is made when a line is plotted from each of these points to the assassination window.

II. PROBABLE LOCATION OF THE THIRD SHOT

Unlike shots one and two, the third shot has been fixed at arrive in the Zauruder films (from 212) a particular frame in the Zapruder films (frame 313), as well as a particular frame in two other films (frame 24 of the Mix film and freme 42 of the Muchmore film). A car should be placed at the point which we believe to be the approximate location corresponding to these frames and then photographed from the point where the three cameramen were standing to establish the accuracy of this location. Distances should be measured from this point to the various points described in part I and angles and distances established between this point and the acsessination window. The car should also be photographed at this point from the assassination window to establish the view which the assessin had when he fired the third shot. Figure Services

FROM THE RATTROAD CORPORATE III. PLOTTING TRAJECTORIES FROM THE RAILROAD OVERPASS

From each of the ground points established in parts I and II trigonometric readings should be taken from a point on either end of the overpass to chart the path which a bullet would travel if fired from those points on the overpass to the rear seat of the car. It should be determined whether a bullet could reach the rear seat without hitting the windshield, and the angle with the horizontal which would the made by a bullet fired from these points to a car located at each of the points on the ground as determined in parts I and II.

A copy of this letter has been sent to Chief Rowley of the Secret Service with a request that the Secret Service provide such essistance in this work as the Commission and your Bureau may require.

The Secret Service has furnished the Commission with photographs, surveys and measurements which we have used in our examination of the films and which wi pleting this project.

We would liber for this the films and which will no doubt be useful to your Eurem in com-

We would like your Bureau to make all necessary errangements for this project. Members of the Bureau assigned to this project abould contact either Mr. Norman Redlich or Mr. Melvin Eisenberg of the

Sincerely,

J. Lee Rankin J. Les Rankin General Counsel