ox.

-Carcano cartridges with tern Cartridge Co. manue panel in CE 139 and des-(See Figs. 1 and 2.)

(See Figs. 1 and 2.) Mannlicher-Carcano carl unloading in the rifle to haracteristics produced in

ved throughout the examice at the National Archives er of the Archives staff acined at the Archives or re-. The panel's materials of bullets and cartridge m identification section at ice Department.

FINDINGS AND CONCLUSIONS OF THE FIREARMS PANEL CONCERNING THE KENNEDY ASSASSINATION

(96) The findings and conclusions were prepared by staff of the House Select Committee on Assassinations based on material submitted by the panel members. The panel has read and accepts those findings and conclusions.

KENNEDY SHOOTING

Evidence examined

(97) The following evidence was examined in connection with the shooting of President Kennedy.

(98) CE 139(77) -One 6.5-millimeter caliber, bolt-action repeating rifle, Manulicher-Carcano Model 1938, serial number C2766. Attached was an Ordnance Optics, Inc. 4X telescopic sight and an adjustable black leather strap.* (See figs. 3A and 3B.)

(100) A visual examination of the rifle revealed pitting, rust and copper oxidation to test-firing, which the panel believed should be removed prior to test-firing. Accordingly, a dry cloth patch was pushed through the bore.

(191) The telescopic sight was attached to a mount, which itself was attached to the left side of the rifle. Mounting facilities were not provided at the time of manufacture. Also attached to the rifle were standard iron sights, placed on the rifle at the time of manufacture.

(102) The rifle was fest-fired by all panel members, using 6.5-millimeter caliber ammunition of Western Cartridge Co. manufacture. Two bullets were test-fired into a horizontal water recovery tank. Further tests were conducted by loading four cartridges into the CE 375 cartridge clip and inserting it into the magazine of the rifle. The contridges were worked through the rifle's mechanism and ejected without being fired. When the last cartridge was chambered, the cartridge clip remained in the magazine instead of falling out as it is designed to do.

(103) CE 141.—One 6.5-millimeter caliber cartridge of Western Cartridge Co. manufacture, found in the CE 139 rifle. (See fig. 4.)

(104) CE 351.—One damaged automobile windshield removed from the Presidential limousine. (See fig. 5.)

(105) *CE* 399.- One fired 6.5-millimeter caliber full metal-jacketed bullet, found on a stretcher in the emergency area of Parkland Hospital. The bullet weight was found to be 157.7 grains. (7.2) In the same box as the bullet was a tiny fragment, which was too small to weigh or otherwise examine. (See figs. 6A and 6B.)

€ 158.6 when it Martial FBILit-Gel Domptes remained for testing in otherway missing control way missing control way winks c. 4 m.

HSCA

^{*}The CE 139 rifle was physically examined and found to be operable. It had **not been properly** cleaned, maintained or lubricated. The rifling of the barrel was four lands and four grooves, right twist. The magazine was a non-detachable box, clip-fed type, with a 6-cartridge capacity. The trigger pull was determined by the panel to be approximately 3 pounds.